



DIGITAL THERMOMETERS

T-Handle Digital Thermometer Model Accu-Temp™ T (F and C)

The Accu-Temp™ T is a rugged thermistor stem probe thermometer designed with penetration of tougher materials in mind. The Accu-Temp™ T has a convenient Fahrenheit/Celsius selectable a wide reading range of -58° F to



+302° F (-50° C to +150° C). Durable and accurate, this digital thermometer also has an easy-to-read LCD and a low battery indicator with a hold function to make it one useful for monitoring and survey work.



Please specify whether you are ordering a C or an F unit.

Inquire about Global Sensors calibration maintenance programs. We calibrate what we sell.

Global Sensors, LLC
79 McAdenville Road
Belmont, NC 28012

866.402-8282 (toll free)
704.825.8282
704.825.0191 (FAX)
www.global-sensors.com

Specifications



Range
+58° F to +302° F (-50° C to +150° C)

Accuracy
+1.8° F (+1.0° C)

Operating Range (Case)
-14° F to +104° F (-50° C to +40° C)

Response Time
1 second in liquid; 12 seconds in air

Display
Easily read LCD; "HOLD/TEST" button for indefinite retention of readings when H/T button is depressed then release to display "Hold" status

Auto-Off
1 Hour

Battery Type and Specification
Unit is supplied with a 1.5V button type (G13/A76 size of equivalent). User replaceable. Battery life under normal usage: 2 years.

Sensor Device
Unit is supplied with a fixed stainless steel piercing probe (see Dimensions for detailed information on the standard probe).

Dimensions
Total Length: 3.4 in (86mm)
Probe Length: 4.9" (123mm). Stainless steel shaft is reinforced for durability
Probe Diameter: 0.125" (3.2mm)

Enclosure and Case
Waterproof casing of durable ABS plastic. Battery compartment O-ring sealed

Probe Casing:
Protective sheath with pen clip to protect and store the stainless steel probe

Temperature Display
Unit is switchable: ° F and ° C

Resolution
0.1° F (0.1° C)

Warranty
90 Days

Price
\$18.00 each. Volume discounts are available contact our sales line for a price quote.